

NETWORK DAMPENING PRESS COVER CLEANER

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: Photo Systems, Inc. Product Name: **DAMPENING PRESS COVER CLEANER**
 Product Number: **871-0002** Date Prepared: 09/26/2007
 Customer Information Phone Number: 1-800-521-4042
 CHEMTREC®: 24 Hour Emergency Transport Phone Number: **1-800-424-9300**

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	OHSA PEL	ACGIH TLV	Weight %
ANIONIC SURFACTANTS	Mixture	N.E.	N.E.	10-15
2-BUTOXYETHANOL	111-76-2	25 ppm TWA(skin)	25 ppm	3-6
DIPROPYLENE GLYCOL	34590-94-8	100 ppm	100 ppm	1-3
SODIUM CARBONATE	5968-11-6	N.E.	N.E.	1-3
NONIONIC SURFACTANTS	Mixture	N.E.	N.E.	1-3
DIETHANOLAMINE	111-42-2	3 ppm TWA	0.46 ppm(skin)	< 2

3. HAZARDOUS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause irritation or permanent damage.

Inhalation: May cause irritation to nasal membranes and respiratory tract.

Ingestion: Alkaline nature of solution may cause irritation or corrosion to digestive tract.

Skin Contact: May cause irritation upon contact.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, dermatitis, difficulty breathing, abdominal pain, skin irritation, coughing, nausea, diarrhea.

4. FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

Inhalation: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If irritation develops, remove to fresh air and get medical attention if cough or other symptoms develop.

Ingestion: If swallowed, DO NOT induce vomiting. Give large quantities of water. Call a physician or poison control center immediately.

Skin Contact: Wash affected area with soap and water for at least fifteen minutes. If irritation occurs, seek medical attention.

Aggravated Medical Conditions: Skin contact may aggravate an existing dermatitis.

Supplemental Health Information: None of the components in this product is listed by IARC, NTP, or OSHA as carcinogen.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

Flash Point: 200°F Flash Point Method: TCC Auto ignition: N.E.

LEL: N.E. UEL: N.E.

Extinguishing Media: Foam, water fog, carbon dioxide, dry chemical.

Special Fire-Fighting Procedures: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece in positive pressure mode.

Unusual Fire And Explosion Hazards: Avoid contact with metals.

Combustion Products: Ammonia will be released. Heat may release carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Spilled Or Released: Review fire and explosion hazards and safety precautions before proceeding with cleanup. Use appropriate personal protective equipment. Avoid contact with skin and eyes. Stop the spillage. Dike the spill. Prevent liquid from entering sewers, waterways or low areas. Absorb spillage in inert material. Soak up with sawdust, sand, or other absorbent material. Remove non-usable solid material and/or contaminated soil for disposal in an approved and permitted landfill. Discharge to sewer requires approval of permitting authority and may require pre-treatment. Contaminated surfaces should be cleaned using water.

7. HANDLING AND STORAGE

Precautions To Be Taken In Handling And Storage: Store in a cool, dry, well ventilated area. Keep containers closed. Do not store with incompatible materials. Do not store or consume food, drink, or tobacco where they may become contaminated with this material.

Other Precautions: All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Triple rinse before disposal. Dispose of in a licensed facility.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: When this product is used in the intended way, no respiratory protection is anticipated to be necessary.

Ventilation: Local exhaust ventilation is recommended. Ventilation must be adequate to keep hazardous ingredients below their exposure limits.

Protective Gloves: Latex, rubber, or neoprene waterproof gloves are recommended.

Eye Protection: Safety glasses with side shields (or goggles).

Other Protective Clothing or Equipment: Rubber or plastic apron.

Work/Hygienic Practices: Use good personal hygiene when handling this product. Wash hands after use, before smoking, or using the toilet.

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Exposure Guidelines: See Section 2.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance And Odor: Clear, slight pine odor. Solubility In Water: Complete
Boiling Point: >212° F Vapor Pressure: N.E. Specific Gravity: 1.04
Melting Point: Not applicable Freezing Point: N.E. Evaporation Rate: < 1
Vapor Density: N.E. Percent Volatile: 81.53 Ph: 12.00
Molecular Weight: Not applicable Pounds Per Gallon: 8.66
V.O.C. = 112.56 g/L or 10.82% or 0.94 lbs/gal.

10. STABILITY AND REACTIVITY

Stability: Stable
Conditions To Avoid: Avoid high temperatures.
Incompatibility: Strong acids.
Hazardous Decomposition Or By Products: Carbon monoxide and carbon dioxide may evolve under extreme conditions.
Hazardous Polymerization: Will Not Occur
Conditions To Avoid: High temperatures and contact with metals.

11. TOXICOLOGICAL INFORMATION**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS**

Discharge, treatment or disposal may be subject to Federal, State (provincial in Canada) or local laws.

14. TRANSPORT INFORMATION

DOT Class: NOT REGULATED
Hazard Class: NONE
UN No.: NOT APPLICABLE
Packing Group:
Guide No:
Ship Name: NOT REGULATED

15. REGULATORY INFORMATION

TSCA: All ingredients in this finished product are listed on the EPA TSCA INVENTORY.
SARA TITLE III: Diethanolamine is listed under Sara Title 313.
CALIF. PROP. 65: This product contains mixtures which include Ethylene Oxide (Cas # 75-21-8). The following information is required by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986, or Proposition 65. This regulation does not address di minimus levels; therefore, even trace amounts of the chemicals included on Proposition 65's list of chemicals known to the State of California to cause cancer or reproductive toxicity must be noted with the "Safe Harbor" wording. WARNING: This product contains Ethylene Oxide – known to the State of California to cause cancer, birth defects or other reproductive harm.
CARCINOGENICITY: NONE OF THE COMPONENTS IN THIS CHEMICAL IS ABOVE THE MINIMUM AMOUNT LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

SCAQMD Rule 443.1

Photochemically Reactive: No
Maximum Grams of VOC per Liter: 112.56 g/L
Vapor Pressure: N.E. mm Hg@ 20 Degrees C

16. OTHER INFORMATION (HMIS)

Health: 2
Flammability: 0
Reactivity: 0
Protective: C

OTHER ADDITIONAL INFORMATION: The information contained herein is based on the data available to us and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for the injuries from the use of the product described herein.