



Quality Developer System Cleaner Kit

This rapid acting, industrial-strength processor cleaner removes chemistry residue, tar, silver deposits, emulsion and algae from developer and wash tank rollers from all types of conventional plate and film processors. This product is also suitable for use on plate processing sections of ITEK and MITSUBISHI camera plate-makers using Mega or Silvermaster products.

This ready-to-use processor-cleaning kit contains:

- ◆ Detailed "How to Use" instructions
- ◆ 2-32oz. Part A Cleaner
- ◆ 2-32oz. Part B Cleaner
- ◆ 2-32oz. Neutralizer

One kit is enough to make (4) four working gallons of solution. This developer system cleaner is compatible with all brands of photo-chemistry, but must be carefully and fully rinsed away before refilling the developer tanks for use.

This product contains **NO chromium compounds** and the performance surpasses its competition.

| PRODUCT | PART# | SIZE |
|------------------------------|--------------|--|
| Developer System Cleaner Kit | 28560-49 | 6X1 quart bottles (Makes 4 gallons) |

If you have any additional questions, please call our Technical Specialist
1-800-262-9333.

QUALITY DEVELOPER SYSTEM CLEANER KIT

Read the following instructions before using this product.

CAUTION...

- ◆ DO NOT USE DEVELOPER SYSTEM CLEANER IN FIXER TANK.
- ◆ DO NOT RUN SYSTEM CLEANER THROUGH THE REPLENISHMENT SYSTEM.
- ◆ DO NOT MIX THE CLEANER WITH THE NEUTRALIZER OR OTHER PROCESSOR SOLUTION.

It is important to rinse the developer tank thoroughly before refilling for use. Flush the tank rack and recirculation system with water BEFORE USING SYSTEM CLEANER.

Use caution and wear appropriate protective clothing, gloves and equipment when using or handling solutions.

NOTE: THE DEVELOPER SYSTEM CLEANER CAN BE USED IN THE WASH SECTION OF THE PROCESSOR TO REMOVE ALGAE SLUDGE. RINSE WASH TANK AND RACK THOROUGHLY THEN FOLLOW DIRECTIONS AS STATED FOR CLEANING THE DEVELOPER SECTION.

MIXING INSTRUCTIONS

To make 2 gallons working strength cleaner solution, add 1 quart part **A** to a tank filled with 1.5 gallons (6 quarts) cool water and mix, then add 1 quart part **B** and mix thoroughly.

TO CLEAN RACK AND TANKS: DISCONNECT OR SHUT-OFF REPLENISHMENT TANK HOSES. DO NOT ALLOW DEVELOPER TO BE PUMPED INTO DEVELOPER TANK WHILE USING CLEANING SOLUTION.

1. Completely drain the developer from the machine and remove any filters from the recirculation system.
2. Thoroughly rinse the developer tank and racks. Fill the tank with water and circulate, then completely drain the rinse water. If processor racks are made with hollow rollers, clean the rack outside the machine.
3. Fill the developer tank with working strength cleaner and circulate for 5-30 minutes.
4. Before draining cleaner, add the 1 quart bottle of **neutralizer**, circulate, then completely drain the solution.
5. Fill the tank with water and circulate, then completely drain water.
6. Replace any filters and refill tank with developer. Open or turn on Developer replenishing lines.

TO CLEAN RACKS OUTSIDE THE MACHINE

1. Remove racks from the machine and thoroughly rinse with water.
2. Use a suitable container or wash bottle filled with working strength cleaner to direct a stream of cleaner onto rack. Use a sponge to clean. Do not use a spray bottle.
3. Thoroughly rinse racks with water and allow to drain.
4. Add the **neutralizer** to the used working strength cleaner and mix. Drain the used solution.
5. Replace the racks in the machine and refill with the tank developer.

FOR TECHNICAL SUPPORT
CALL 800-262-9333